



Height Adjustable Bathtub

Hygiene Equipment
Designed for People



Specifications for Height Adjustable Bathtub

Specifications for basic height adjustable bathtub

- Electric height adjustable to enable ergonomic working methods for the caregiver
- Bath must be designed to work with a mobile patient lift system to safely manage the entire bathing cycle
- Bathtub to be manufactured in fiber glass
- Control panel to be manufactured in fiber glass
- Control panel with electronic control functions operated by push buttons or touchpad
- Lighted display to show activated panel options
- Bathtub must include thermostatic mixing valve
- Digital LED thermometer for shower and bathtub water temperature when filling
- Bathtub must include adjustable foot support and include patient head pillow
- Bathtub must include a patient shower with hose and shower handle
- Control panel to be activated with special safety on/off key to avoid improper use by patient
- Push button controlled temperature display – shower, filling and tub water
- Push button controlled shower on/off

Specification text to add for CLEANING system

- Integrated disinfection cleaning system
- Disinfectant storage & Key-locked

Specification text to add for WHIRLPOOL system

- Push button controlled whirlpool on/off
- Single whirlpool outlet that can be quickly fully cleaned and disinfected
- Water and air adjustment easily adjusted via the air flow control knob
- Single suction grid

Specification text to add for AUTOFILL system

- Push button controlled auto fill on/off
- Autofill with dual preset fill levels to choose from

Dimension and load specifications

- | | | |
|-------------------------------------|-------------------------------------|-------------------------------------|
| • Operating Height Range (bathtub): | Min: 600 mm/23 ^{1/4} inch | Max: 1000 mm/39 ^{2/5} inch |
| • Length (bathtub): | Min: 2250 mm/88 ^{1/4} inch | Max: 2350 mm/92 ^{1/2} inch |
| • Length (inside bathtub) | Min: 1750 mm/69 inch | |
| • Width (bathtub): | Min: 800 mm/31 ^{1/2} inch | Max: 850 mm/33 ^{1/2} inch |
| • Weight Limit (patient): | 150 kg / 330 lbs. | |

Head Office

TR Equipment AB, Sweden
Phone: +46 140 38 50 60
info@trequipment.se
www.trequipment.com

Group Subsidiaries

TR Group Inc, US, Phone: +1 (800) 752 6900
TR Equipment Ltd, UK, Phone: +44 (0) 844 335 8386
TRanspoRehaMed GmbH, Germany, Phone: +49 (0) 212 645850-0



TR EQUIPMENT